



# ÖLFLEX® CLASSIC 115 CY

PVC

ÖLFLEX® CLASSIC 115 CY - PVC  
U<sub>0</sub>/U: 300/500V

가

PVC

CPR: [www.lappkabel.com/cpr](http://www.lappkabel.com/cpr)

가

EMC-



EMC-

( )  
WTG( )

(24.04.2024)

# ÖLFLEX® CLASSIC 115 CY

: IEC 60332-1-2  
T1

( . 250 /km, 30 MHz )

EN 50525-2-51

PVC LAPP P8/1 가

(RAL 7001) PVC

ETIM 5:

ETIM 5.0 Class-ID: EC000104  
ETIM 5.0

ETIM 6:

ETIM 6.0 Class-ID: EC000104  
ETIM 6.0 Class :

:

Black with white numbers acc. to VDE 0293-334

:

IEC 60228/VDE 0295 class 5

WTG :

TW-0 & TW-1, T0

:

: 20 x

: 6 x

:

U0/U: 300/500 V

:

Core/core: 4000 V

Core/screen: 2000 V

:

G = GN/YE

X = GN/YE

:

: -5°C ~ +70°C

: -40°C +80°C

가 가 ( . ) 가 .  
[www.lappkabel.de/en/cable-standradlengths](http://www.lappkabel.de/en/cable-standradlengths)

: 30 kg or 250 m,  
(e.g. 1 x 500 m or 5 x 100 m ).

가 VAT 가 가 .

(24.04.2024)

# ÖLFLEX® CLASSIC 115 CY

Article number	(CORE) / (mm <sup>2</sup> )	(mm)	(kg/km)	(kg/km)
ÖLFLEX® CLASSIC 115 CY				
1136752	2 X 0.5	5.8	36	54
1136003	3 G 0.5	6.1	43	63
1136753	3 X 0.5	6.1	43	63
1136004	4 G 0.5	6.5	49	71
1136754	4 X 0.5	6.5	49	71
1136005	5 G 0.5	7	57	86
1136755	5 X 0.5	7	57	86
1136007	7 G 0.5	7.5	69	105
1136757	7 X 0.5	7.5	69	105
1136012	12 G 0.5	9.9	104	200
1136762	12 X 0.5	9.9	104	200
1136018	18 G 0.5	11.5	141	275
1136768	18 X 0.5	11.5	141	275
1136025	25 G 0.5	13.4	211	350
1136775	25 X 0.5	13.4	211	350
1136802	2 X 0.75	6.2	43	56
1136103	3 G 0.75	6.5	52	70
1136803	3 X 0.75	6.5	52	70
1136104	4 G 0.75	7	61	95
1136804	4 X 0.75	7	61	95
1136105	5 G 0.75	7.7	72	108
1136805	5 X 0.75	7.7	72	108
1136107	7 G 0.75	8.3	89	127
1136807	7 X 0.75	8.3	89	127
1136112	12 G 0.75	10.9	138	232
1136118	18 G 0.75	12.7	211	315
1136125	25 G 0.75	14.8	280	435
1136825	25 X 0.75	14.8	280	435
1136852	2 X 1.0	6.5	51	71
1136203	3 G 1.0	6.8	62	86
1136853	3 X 1.0	6.8	62	86
1136204	4 G 1.0	7.3	74	98
1136854	4 X 1.0	7.3	74	98

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02\_03\_16

Article number	(CORE) / (mm <sup>2</sup> )	(mm)	(kg/km)	(kg/km)
1136205	5 G 1.0	8.1	88	121
1136855	5 X 1.0	8.1	88	121
1136207	7 G 1.0	8.8	112	147
1136857	7 X 1.0	8.8	112	147
1136212	12 G 1.0	11.5	185	285
1136218	18 G 1.0	13.9	268	395
1136225	25 G 1.0	15.9	354	486
1136902	2 X 1.5	7.1	65	86
1136303	3 G 1.5	7.5	82	112
1136903	3 X 1.5	7.5	82	112
1136304	4 G 1.5	8.2	100	135
1136904	4 X 1.5	8.2	100	135
1136305	5 G 1.5	8.9	119	148
1136905	5 X 1.5	8.9	119	148
1136307	7 G 1.5	9.9	154	192
1136907	7 X 1.5	9.9	154	192
1136312	12 G 1.5	13	268	365
1136318	18 G 1.5	15.6	373	520
1136325	25 G 1.5	17.9	530	734
1136334	34 G 1.5	20.8	683	944
1136403	3 G 2.5	8.9	118	151
1136404	4 G 2.5	9.9	147	188
1136405	5 G 2.5	11	176	270
1136407	7 G 2.5	11.9	253	340
1136412	12 G 2.5	16	355	540
1136418	18 G 2.5	19	569	782
1136425	25 G 2.5	22.2	827	1358
1136504	4 G 4.0	11.6	248	305
1136507	7 G 4.0	14.4	355	500
1136604	4 G 6.0	14.2	343	440
1136607	7 G 6.0	17	505	672
1136614	4 G 10.0	17.2	495	680
1136615	5 G 10.0	19.5	592	824
1136624	4 G 16.0	20.2	800	1050

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02\_03.16



# ÖLFLEX® CLASSIC 115 CY

Article number	(CORE) / (mm <sup>2</sup> )	(mm)	(kg/km)	(kg/km)
1136625	5 G 16.0	22.6	895	1285
1136634	4 G 25.0	25.1	1075	1413
1136635	5 G 25.0	28	1400	1976
1136638	4 G 35.0	28	1576	2070

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02\_03.16