



SILVYN® LTP 45° M

SILVYN® LTPW-M

IP66/67/68/69



SILVYN®
LTP
가

45° , 6

ETIM 5:

ETIM 5.0 Class-ID: EC001180
ETIM 5.0 Class :

ETIM 6:

ETIM 6.0 Class-ID: EC001180
ETIM 6.0 Class :

:

IEC EN 61386-23

:

:

: PA ()

가:

IP66
IP67
IP68 (5 bar)

(23.04.2024)



SILVYN® LTP 45° M

IP69

-50°C ~ +135°C

:

가 VAT 가 가 .

(23.04.2024)



SILVYN® LTP 45° M

| | | SW (mm) | (thread) (mm) | SILVYN® LTP | / PU |
|----------------------|------------|---------|---------------|-------------|------|
| SILVYN® LTP 45° M | | | | | |
| 55510300 | 20 x 1.5/1 | 24.0 | 13 | 16 | 10 |
| 55510301 | 20 x 1.5/2 | 24.0 | 13 | 20 | 10 |
| 55510302 | 25 x 1.5 | 30.0 | 14 | 25 | 10 |
| 55510303 | 32 x 1.5 | 36.0 | 15 | 32 | 2 |
| 55510304 | 40 x 1.5 | 47.0 | 18 | 40 | 1 |
| 55510305 | 50 x 1.5 | 61.0 | 18 | 50 | 1 |
| 55510306 | 63 x 1.5 | 67.0 | 20 | 63 | 1 |

(23.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16