

# SILVYN® LTPG-M

SILVYN® LTPG-M

IP66/67/68/69



SILVYN® LTP

가

(23.12.2023)

# SILVYN® LTPG-M

6

ETIM 5:	ETIM 5.0 Class-ID: EC001180
	ETIM 5.0 Class :
ETIM 6:	ETIM 6.0 Class-ID: EC001180
	ETIM 6.0 Class :
:	IEC EN 61386-23
:	:
가:	: PA ( )
	IP66
	IP67
	IP68 (5 bar)
	IP69
:	-50°C ~ +135°C

가 VAT 가 가 .

(23.12.2023)



# SILVYN® LTPG-M

		SW (mm)	(thread) (mm)	SILVYN® LTP	/ PU
SILVYN® LTPG-M					
55510200	12 x 1.5	20.0	10	10	10
55510210	16 x 1.5/1	20.0	10	12	10
55510220	16 x 1.5/2	24.0	10	16	10
55510230	20 x 1.5/1	24.0	12	16	10
55510240	20 x 1.5/2	26.0	12	20	10
55510250	25 x 1.5	33.0	14	25	10
55510260	32 x 1.5	40.0	15	32	2
55510270	40 x 1.5	50.0	16	40	1
55510280	50 x 1.5	58.0	16	50	1
55510290	63 x 1.5	70.0	20	63	1

(23.12.2023)

©2023 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02\_03.16