

SILVYN® LTPS-M

SILVYN® LTPS-M

IP66/67/68/69



SILVYN® LTP

가

(24.04.2024)



SILVYN® LTPS-M

6 , 가

ETIM 5:

ETIM 5.0 Class-ID: EC001180

ETIM 5.0 Class :

ETIM 6:

ETIM 6.0 Class-ID: EC001180

ETIM 6.0 Class :

:

IEC EN 61386-23

:

:

: PA ()

가:

IP66

IP67

IP68 (5 bar)

IP69

:

-50°C ~ +135°C

가 VAT 가 가 .

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16



SILVYN® LTPS-M

		SW (mm)	(thread) (mm)	SILVYN® LTP	/ PU
SILVYN® LTPS-M					
55510600	16 x 1.5/1	20.0	10	12	10
55510610	16 x 1.5/2	24.0	10	16	10
55510620	20 x 1.5/1	24.0	10	16	10
55510630	20 x 1.5/2	26.0	10	20	10
55510640	25 x 1.5	33.0	12	25	10
55510650	32 x 1.5	40.0	13	32	2

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16