

SILVYN® MSK-M ATEX BRUSH

SILVYN® MSK-M ATEX BRUSH - ATEX

IECEX
360°



SKINTOP®



(22.02.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16

SILVYN® MSK-M ATEX BRUSH

"e" , , "t"

가 가

SILVYN® SKINTOP®

SILVYN®

DIN EN 60423

To be used in Ex environment only in combination with metal conduits without a plastic jacket

ETIM 5:

ETIM 5.0 Class-ID: EC001180

ETIM 5.0 Class :

ETIM 6:

ETIM 6.0 Class-ID: EC001180

ETIM 6.0 Class :

:

CE 0637 Ex II 2G

Ex eb IIC Ex II 1D

Ex ta IIIC

IECEx IBE 13.0033X

:

:

:

: CR/NBR

: TPE

EMC :

:

DIN EN 60079-0

DIN EN 60079-7

DIN EN 60079-31

가:

: IP 68

:

IP 40 with SILVYN® AS, EDU-AS, EMC AS-CU

:

-30°C +90°C

가 VAT 가 가 .

(22.02.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16

SILVYN® MSK-M ATEX BRUSH

		Clamping range in mm	(mm)	OØ (mm)	/ PU
SILVYN® MSK-M ATEX BRUSH for SILVYN® AS					
55506042	25 x 1.5	9.0 - 17.0	14.5	21	10
55506043	32 x 1.5	11.0 - 21.0	19.5	27	1
55506044	40 x 1.5	19.0 - 28.0	26.5	36	1
55506045	50 x 1.5	27.0 - 35.0	36	45	1
55506030	63 x 1.5	34.0 - 45.0	45.5	56	1
SILVYN® MSK-M ATEX BRUSH for SILVYN® EDU-AS / EMC AS-CU					
55506031	25 x 1.5	9.0 - 17.0	14.5	21	10
55506032	32 x 1.5	11.0 - 21.0	19.5	27	1
55506033	40 x 1.5	19.0 - 28.0	26.5	36	1
55506034	50 x 1.5	27.0 - 35.0	36	45	1
55506035	63 x 1.5	34.0 - 45.0	45.5	56	1