

SILVYN® FPAX R

SILVYN® FPAX R - T/Y

SILVYN® FPAX T/Y



SILVYN® FPAX T/Y

SILVYN® FPAS :

ETIM 5:

ETIM 5.0 Class-ID: EC001172

ETIM 5.0 Class :

ETIM 6:

ETIM 6.0 Class-ID: EC001172

ETIM 6.0 Class :

:

(RAL 9005), UV

(24.04.2024)

©2024 Lapp Group - all rights reserved.

<http://lappkorea.lappgroup.com>

data sheet

PN 0456 / 02_03.16



SILVYN® FPAX R

: PA66
Polyester Elastomer
가: IP66
IP67
IP68 (2 bar)
IP69
: -50°C ~ +135°C

가 VAT 가 가 .

(24.04.2024)



SILVYN® FPAX R

	()	SILVYN®FPAX T/Y	SILVYN® FPAS	/ PU
SILVYN® FPAX R				
55507360	16-13	16	13	5
55507361	21-16	21	16	5
55507363	28-16	28	16	5
55507362	28-21	28	21	5
55507366	34-16	34	16	5
55507365	34-21	34	21	5
55507364	34-28	34	28	5
55507369	42-21	42	21	3
55507368	42-28	42	28	3
55507367	42-34	42	34	3