

# SILVYN® KLICK GPZ-M

SILVYN® KLICK GPZ-M - SILVYN® RILL

가



가  
가

SILVYN® RILL PA 6

SILVYN® RILL PA 12

가

(23.12.2023)



# SILVYN® KCLICK GPZ-M

UL FILENUMBER E308201

가

PG threaded versions are to be found in the online catalogue

ETIM 5:	ETIM 5.0 Class-ID: EC001176
	ETIM 5.0 Class :
ETIM 6:	ETIM 6.0 Class-ID: EC001176
	ETIM 6.0 Class :
:	(RAL 7001)
	(RAL 9005), UV
:	PA6
가:	IP 68
	IP 69
:	-40°C ~ +115°C

가 VAT 가 가 .

(23.12.2023)

		Clamping range in mm	SW (mm)	(thread) (mm)	(mm)		SILVYN® RILL	/ PU
SILVYN® KLICK, GPZ-M								
55500800	12 x 1.5	4 - 6.5	16	8	6.5	10	10	20
55500810	16 x 1.5	5 - 9.5	18	8	9.5	13	13	20
55500820	20 x 1.5	8 - 12	24	8	13	15.8	16	20
55500830	25 x 1.5	11 - 16	27	8	16	21.2	21	10
55500840	32 x 1.5	15 - 21	34	10	18	28.5	28	10
55500850	40 x 1.5	16 - 26	40	10	25	34.5	34	10
55500860	50 x 1.5	27 - 35	55	12	32	42.5	42	10
55500870	63 x 1.5	32 - 42	65	12	44	54.5	54	10
SILVYN® KLICK, GPZ-M								
55500805	12 x 1.5	4 - 6.5	16	8	6.5	10	10	20
55500815	16 x 1.5	5 - 9.5	18	8	9.5	13	13	20
55500825	20 x 1.5	8 - 12	24	8	13	15.8	16	20
55500835	25 x 1.5	11 - 16	27	8	16	21.2	21	10
55500845	32 x 1.5	15 - 21	34	10	18	28.5	28	10
55500855	40 x 1.5	16 - 26	40	10	25	34.5	34	10
55500865	50 x 1.5	27 - 35	55	12	32	42.5	42	10
55500875	63 x 1.5	32 - 42	65	12	44	54.5	54	10